

व्यावसायिक परीक्षण रिपोर्ट (प्रारंभिक)
COMMERCIAL TEST REPORT (Initial)



संख्या / No.: Imp. 275/354
माह / Month: February 2020



THIS TEST REPORT IS VALID UPTO 28/02/2027



GREENSYSTEM ROTARY TILLER (ROTAVATOR), MODEL: RT5026L
MULTI SPEED, GEAR DRIVE, CENTRALLY MOUNTED



भारत सरकार
GOVT OF INDIA

कृषि एवं किसान कल्याण मन्त्रालय

MINISTRY OF AGRICULTURE & FARMERS WELFARE

कृषि, सहकारिता एवं किसान कल्याण विभाग

DEPARTMENT OF AGRICULTURE, COOPERATION & FARMERS WELFARE

उत्तर पूर्वी क्षेत्र कृषि यंत्र प्रशिक्षण एवं परीक्षण संस्थान

NORTH EASTERN REGION FARM MACHINERY TRAINING & TESTING INSTITUTE

विश्वनाथ चारिआलि, जिला-विश्वनाथ (असम)

BISWANATHI CHARIALI: BISWANATHI: ASSAM, PIN - 784 176

[AN ISO 9001:2015 CERTIFIED INSTITUTION]

Ph. No. 03715-222094

Website: <http://nerfntti.nic.in>

Fax No: 03715-230358

E-Mail: fnti-ner@nic.in




1	2	3	4	5	6	7
v	Country of origin	Evaluative	Should be provided on rotary tiller (Rotavator)	--	India	Yes
vi	Year of manufacture			--	Not Provided	No
vii	Chassis Serial Number			--	Provided	Yes
viii	Recommended PTO speed of Prime mover(rpm)			--	Not Provided	No
ix	Maximum PTO power requirement, kW			--	Not Provided	No
8	Category of breakdowns/ defects					
	Category of breakdowns	Category Evaluative/ Non Evaluative	Requirements	As Observed	Whether meets the requirements (Yes/ No)	
i	Critical breakdowns	Evaluative	No critical breakdown	None	Yes	
ii	Major breakdown	Evaluative	Not more than one and neither of them should be repetitive in nature.	None	Yes	
iii	Minor breakdowns	Evaluative	Not more than three and frequency of each should not be more than two.	None	Yes	
iv	Total breakdowns	Evaluative	In no case, the total no of breakdown should exceed four, i.e. (1 major + 3 minor) or 4 minor breakdowns	None	Yes	

11. COMMENTS AND RECOMMENDATIONS

- 11.1** Dimensions of PIC of implement does not conform to IS: 4931-1995 and it should be looked into for corrective action.
- 11.2** Chemical composition of rotor blades does not conform to IS: 6690-2002. The percentage of carbon and manganese content in composition of rotary tiller blade material was recorded as 0.303 and 1.264, respectively. The carbon content was on lower side and manganese content was on higher side when compared with the relevant Indian Standard. Moreover, the hardness of Shank & Edge portion of rotor blades also does not conform to relevant Indian Standard. It is therefore, recommended that the material of rotary tiller blade should be improved and shall be provided as per requirement of Indian Standard.
- 11.3** In dry land operation average depth of cut was recorded as 8.30 cm which does not meet the requirement of Indian Standard.

11.4 Technical literature:

Operator cum Service Manual & Parts Catalogue was provided along with the machine during the course of testing. It is further recommended to bring out these manuals in hindi and other vernacular languages as per IS: 8132-1999

TESTING AUTHORITY



(M.R. PATIL)

AGRICULTURAL ENGINEER



(J.P. MANDAL)

SENIOR AGRICULTURAL ENGINEER



(K.K. NAGLE)

DIRECTOR

Draft test report compiled by - Shri Khagendra Bora, STA

12. APPLICANT'S COMMENTS

Para No	Our Reference	Applicant's Comments
12.1	11.1	The dimension of PIC of implement will be modified to confirm to IS 4931-1995.
12.2	11.2	Rotary Tiller blades are made of "BORON" steel which is better than Carbon & Silicon Manganese steel Referred in IS 6690- 2002. Chemical compositions and Hardness of Rotavator Blade are maintaining as per "BORON" steel.